



PT SUPREME CABLE

MANUFACTURING & COMMERCE Tbk

(PT SUCACO Tbk)



Product Catalogue **FLEXIBLE CABLE**

www.sucaco.com



@supreme_cable



@supreme_cable

**QUALITY CABLE
YOU CAN TRUST**

Scan For
Catalogue





SUPREME CABLE

Company Background

Specializing in the cable business for over 53 years, PT SUPREME CABLE MANUFACTURING & COMMERCE Tbk or abbreviated as PT SUCACO Tbk has grown steadily to become one of Indonesia's largest and leading cable manufacturers.

Today, PT SUCACO Tbk has grown to become a reliable partner in the cable industry. In addition, the Company is also a respected corporation with a healthy financial position that makes contribution in building national infrastructures with it's international reputation.

The Company is also involved through it's affiliated companies, in various line of business. The company has a Quality Assurance Program and ISO certificate from SGS international certification body, of ISO 9001 for quality management system, UKAS 0005 for Management System, ISO 14001 for environment management system, and ISO 45001 for occupational health and safety management system.

TABLE OF CONTENT

CABLE TYPE	NO. OF CORE	STANDARD	PAGE
Company Background	~	~	II
TABLE OF CONTENT	~	~	III
NYAF 450/750 Volt	1 Core	SNI 04-6629.3/ SPLN 42-3/ IEC 60227	1
NYMHY 300/500 Volt	2-5 Cores	SNI 04-6629.5/SPLN 42-6-2/IEC 60227-5	2
NYHY 450/750 Volt	2 Cores	Manufacturing Specification	3
NYHY 450/750 Volt	3 Cores	Manufacturing Specification	4
NYHY 450/750 Volt	4 Cores	Manufacturing Specification	5
NYHY 450/750 Volt	Control Cable	Manufacturing Specification	6
Cu/PVC/TCWB/PVC (LiYCY) 300/500 V	2-5 Cores	Manufacturing Spec. / IEC 60227.7	7
Cu/PVC/TCWB/PVC (LiYCY) 300/500 V	>5 Cores	Manufacturing Spec. / IEC 60227.7	8-10
CONVERSION TABLE	~	~	11

NYAF 450/750 Volt

SNI 04-6629.3/ SPLN 42-3/ IEC 60227-3

SINGLE CORE, FLEXIBLE COPPER CONDUCTOR AND PVC INSULATED CABLE

- Applications** :
1. Fixed internal wiring with low mechanical stress for electrical equipment, machineries, distribution panels, luminaires and other electrical appliances used in dry indoor premises, substitutes NYA
 2. Permanent installation in conduit, inherently flame retardant in compliance with IEC 60332-1

DIMENSIONAL & MECHANICAL DATA

1 Core

Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness	Approximately		Bending Diameter Min	Standard Delivery Length *)
		Insulation	Overall Diameter	Net Weight		
mm ²	pcs	mm	mm	Kg/Km	mm	m
1.5	0.25	0.7	2.9	19	70	100
2.5	0.25	0.8	3.6	31	90	100
4	0.30	0.8	4.1	46	100	100
6	0.30	0.8	4.7	64	110	100
10	0.40	1.0	6.1	110	150	100
16	0.40	1.0	8.0	180	210	2000
25	0.40	1.2	10.1	280	270	1000
35	0.40	1.2	11.2	367	300	1000
50	0.40	1.4	13.8	538	360	1000
70	0.50	1.4	15.1	916	420	1000
95	0.50	1.6	17.9	1,210	500	1000
120	0.50	1.6	19.6	1,525	540	1000
150	0.50	1.8	21.5	1,899	610	1000
185	0.50	2.0	24.6	2,345	690	1000
240	0.50	2.2	26.5	3,066	740	1000
300	0.50	2.4	29.6	3,109	890	1000
400	0.50	2.6	35.6	3,850	990	500

*) Standart delivery lenght : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity at 30°C Max		Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min			
			In Pipe	In Air	
mm²	Ω/Km	MΩ.Km	mm	Kg/Km	kA
1.5	13.3	10	15	24	70
2.5	7.98	9	20	32	90
4	4.95	7	25	42	100
6	3.30	6	33	54	110
10	1.91	6	45	73	150
16	1.21	5	61	98	210
25	0.780	4	83	128	270
35	0.554	4	103	158	300
50	0.386	4	132	197	360
70	0.272	3	165	245	420
95	0.206	3	197	290	500
120	0.161	3	235	345	540
150	0.129	3	-	390	610
185	0.106	3	-	445	690
240	0.0801	3	-	525	740
300	0.0641	3	-	605	890
400	0.0486	3	-	725	990

Core identification : Green-Yellow, Blue, Black, Yellow, Red, Green, White or Brown.
Test Voltage : 2500 VAC/ 5 minutes.

Other sizes, core identification and packing lenght are available upon request.

NYMHY 300/500 Volt

SNI 04-6629.5/SPLN 42-6-2/IEC 60227-5

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED AND SHEATHED CABLE

- Applications** :
1. Power cord or internal wiring with low mechanical stress for electrical equipments, machineries, luminaires and other portable appliances used in dry indoor premises.
 2. Permanent exposed wiring in humid environment, installation in tray or under plaster for industrial three phase 380 - 415 VAC or single phase 220 - 240 VAC multipurpose applications, inherently flame retardant in compliance with IEC 60332-1.

DIMENSIONAL & MECHANICAL DATA

2, 3, 4, 5 Cores

No of Cores	Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness		Approximately		Bending Diameter	Standard Delivery Length *)
			Insulation	Outer Sheath	Cable Weight	Overall Diameter		
pcs	mm ²	mm	mm	mm	Kg/Km	mm	mm	m
2	0.75	0.20	0.6	0.8	6.3	54	120	100 or 2000
2	1	0.20	0.6	0.8	6.5	61	120	100 or 2000
2	1.5	0.25	0.7	0.8	7.5	82	140	100 or 2000
2	2.5	0.25	0.8	1.0	9.2	128	180	100 or 2000
3	0.75	0.20	0.6	0.8	6.6	64	120	100 or 2000
3	1	0.20	0.6	0.8	6.9	74	130	100 or 2000
3	1.5	0.25	0.7	0.9	8.1	104	150	100 or 2000
3	2.5	0.25	0.8	1.1	10.0	161	190	100 or 2000
4	0.75	0.20	0.6	0.8	7.3	77	130	100 or 2000
4	1	0.20	0.6	0.9	7.8	92	140	100 or 2000
4	1.5	0.25	0.7	1.0	9.1	130	170	100 or 2000
4	2.5	0.25	0.8	1.1	10.9	195	200	100 or 2000
5	0.75	0.20	0.6	0.9	8.1	98	150	100 or 2000
5	1	0.20	0.6	0.9	8.5	112	150	100 or 2000
5	1.5	0.25	0.7	1.1	10.1	164	180	100 or 2000
5	2.5	0.25	0.8	1.2	12.2	246	220	100 or 1000

*) Standard delivery length : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max		Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min	2 Cores	3, 4, 5 Cores	
mm ²	Ω.Km	MΩ.Km	A		kA
0.75	26.0	11	9	4	0.10
1	19.5	10	12	10	0.13
1.5	13.3	10	19	17	0.19
2.5	7.98	9	25	22	0.32

Core identification :

- 2 cores by colours : Either Blue, Brown or Blue, Black ;
 3 cores by colours : Either Green-Yellow, Blue, Brown, or Brown, Black, Gray ;
 4 cores by colours : Either Green-Yellow, Brown, Black, Gray, or Blue, Brown, Black, Gray ;
 5 cores by colours : Either Green-Yellow, Blue, Brown, Black, Gray, or Blue, Brown, Black, Gray, Black.

Colour of sheath : White colour

Test Voltage : 1500 VAC/ 5 minutes for insulation thickness ≤ 0,6 mm.
 2000 VAC/ 5 minutes for insulation thickness > 0,6 mm

Other sizes, core identification and packing lengths are available upon request.



NYHYH 450/750 Volt

Manufacturing Specification

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED AND SHEATHED CABLE

- Applications** : 1. Power cord or internal wiring with medium mechanical stress for electrical equipments, machineries, luminaires and other portable appliances used in dry indoor premises
2. Permanent exposed wiring in humid environment, installation in tray or under plaster for industrial three phase 380-415 VAC or single phase 220 - 240 VAC multipurpose applications, inherently flame retardant in compliance with IEC 60332-1.

DIMENSIONAL & MECHANICAL DATA

2 Cores

Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness		Approximately		Minimum Bending Radius	Standard Delivery Length *)
		Insulation	Outer Sheath	Overall Diameter	Cable Weight		
mm ²	mm	mm	mm	mm	Kg/Km	mm	m
0.75	0.20	0.6	0.8	6.3	54	44	100 or 2000
1	0.20	0.6	0.8	6.5	61	46	100 or 2000
1.5	0.25	0.7	0.8	7.5	82	52	100 or 2000
2.5	0.25	0.8	1.0	9.2	128	65	100 or 2000
4	0.30	0.8	1.0	10.2	171	72	2000
6	0.30	0.8	1.1	11.5	228	80	2000
10	0.40	1.0	1.3	14.8	381	104	1000
16	0.40	1.0	1.8	19.8	637	137	1000
25	0.40	1.2	1.8	23.8	944	167	1000
35	0.40	1.2	1.8	25.9	1,194	181	1000
50	0.40	1.4	1.8	30.8	1,693	216	1000

*) Standard delivery length : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
0.75	26.0	11	6	0.09
1	19.5	10	10	0.12
1.5	13.3	10	15	0.17
2.5	7.98	9	20	0.29
4	4.95	7	26	0.46
6	3.30	6	33	0.69
10	1.91	6	45	1.16
16	1.21	5	61	1.84
25	0.780	4	83	2.87
35	0.554	4	103	4.03
50	0.386	4	132	5.75

Core identification :

- 2 cores by colours : Either Blue, Brown or Blue, Black;
3 cores by colours : Either Green-Yellow, Blue, Brown, or Blue, Black, Brown ;
4 cores by colours : Either Green-Yellow, Brown, Black, Gray, or Blue, Brown, Black, Gray ;
5 cores by colours : Either Green-Yellow, Blue, Brown, Black, Gray, or Blue, Brown, Black, Gray, Black ;
>5 cores by colours : Either Green-Yellow and Black with White numbering printing or black with white numbering printing.

- Colour of sheath : Black colours.
Test Voltage : 2500 VAC/ 5 minutes.

Other sizes, core identification and packing lengths are available upon request.



NYHYH 450/750 Volt

Manufacturing Specification

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED AND SHEATHED CABLE

- Applications** :
1. Power cord or internal wiring with medium mechanical stress for electrical equipments, machineries, luminaires and other portable appliances used in dry indoor premises
 2. Permanent exposed wiring in humid environment, installation in tray or under plaster for industrial three phase 380-415 VAC or single phase 220 - 240 VAC multipurpose applications, inherently flame retardant in compliance with IEC 60332-1.

DIMENSIONAL & MECHANICAL DATA


3 Cores

Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness		Approximately		Minimum Bending Radius	Standard Delivery Length *)
		Insulation	Outer Sheath	Overall Diameter	Cable Weight		
mm ²	mm	mm	mm	mm	Kg/Km	mm	m
0.75	0.20	0.6	0.8	6.6	64	46	100 or 2000
1	0.20	0.6	0.8	6.9	73	48	100 or 2000
1.5	0.25	0.7	0.9	8.1	104	57	100 or 2000
2.5	0.25	0.8	1.1	10.0	161	70	100 or 2000
4	0.30	0.8	1.1	11.1	217	78	2000
6	0.30	0.8	1.2	12.4	293	87	1000
10	0.40	1.0	1.4	16.0	489	112	1000
16	0.40	1.0	1.8	20.8	797	146	1000
25	0.40	1.2	1.8	25.4	1,189	178	1000
35	0.40	1.2	1.8	27.7	1,526	194	1000
50	0.40	1.4	1.8	32.9	2,172	230	1000
70	0.50	1.4	1.9	36.8	2,899	258	1000
95	0.50	1.6	2.0	43.4	3,865	304	1000
120	0.50	1.6	2.1	47.4	4,784	332	500
150	0.50	1.8	2.2	51.7	5,887	362	500
185	0.50	2.0	2.4	58.9	7,280	412	500
240	0.50	2.2	2.5	66.3	9,444	464	300

*) Standard delivery length : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
0.75	26.0	11	6	0.09
1	19.5	10	10	0.12
1.5	13.3	10	15	0.17
2.5	7.98	9	20	0.29
4	4.95	7	26	0.46
6	3.30	6	33	0.69
10	1.91	6	45	1.16
16	1.21	5	61	1.84
25	0.780	4	83	2.87
35	0.554	4	103	4.03
50	0.386	4	132	5.75
70	0.272	3	165	8.05
95	0.206	3	197	10.92
120	0.161	3	235	13.80
150	0.129	3	264	17.25
185	0.106	3	297	21.27
240	0.0801	3	351	27.60



NYHYH 450/750 Volt

Manufacturing Specification

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED AND SHEATHED CABLE

- Applications** :
1. Power cord or internal wiring with medium mechanical stress for electrical equipments, machineries, luminaires and other portable appliances used in dry indoor premises
 2. Permanent exposed wiring in humid environment, installation in tray or under plaster for industrial three phase 380-415 VAC or single phase 220 - 240 VAC multipurpose applications, inherently flame retardant in compliance with IEC 60332-1.

DIMENSIONAL & MECHANICAL DATA

4 Cores

Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness		Approximately		Minimum Bending Radius	Standard Delivery Length *)
		Insulation	Outer Sheath	Overall Diameter	Cable Weight		
mm ²	mm	mm	mm	mm	Kg/Km	mm	m
0.75	0.20	0.6	0.8	7.3	77	51	100 or 2000
1	0.20	0.6	0.9	7.8	92	54	100 or 2000
1.5	0.25	0.7	1.0	9.1	130	64	1000
2.5	0.25	0.8	1.1	10.9	195	77	1000
4	0.30	0.8	1.2	12.3	273	86	1000
6	0.30	0.8	1.3	13.8	369	97	1000
10	0.40	1.0	1.5	17.7	616	124	1000
16	0.40	1.0	1.8	22.9	986	160	1000
25	0.40	1.2	1.8	28.0	1,478	196	1000
35	0.40	1.2	1.8	30.5	1,910	214	1000
50	0.40	1.4	1.8	36.6	2,743	256	1000
70	0.50	1.4	1.9	40.9	3,675	287	1000
95	0.50	1.6	2.0	48.3	4,887	338	500
120	0.50	1.6	2.1	52.8	6,063	370	500
150	0.50	1.8	2.2	57.8	7,502	405	500
185	0.50	2.0	2.4	65.6	9,220	459	300
240	0.50	2.2	2.5	74.0	12,010	518	300

*) Standard delivery length : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
0.75	26.0	11	6	0.09
1	19.5	10	10	0.12
1.5	13.3	10	15	0.17
2.5	7.98	9	20	0.29
4	4.95	7	26	0.46
6	3.30	6	33	0.69
10	1.91	6	45	1.15
16	1.21	5	61	1.84
25	0.780	4	83	2.87
35	0.554	4	103	4.03
50	0.386	4	132	5.75
70	0.272	3	165	8.05
95	0.206	3	197	10.92
120	0.161	3	235	13.80
150	0.129	3	364	17.25
185	0.106	3	297	21.27
240	0.0801	3	351	27.60

NYHYH 450/750 Volt

Manufacturing Specification

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED AND SHEATHED CABLE

- Applications** : 1. Power cord or internal wiring with medium mechanical stress for electrical equipments, machineries, luminaires and other portable appliances used in dry indoor premises
2. Permanent exposed wiring in humid environment, installation in tray or under plaster for industrial three phase 380-415 VAC or single phase 220 - 240 VAC multipurpose applications, inherently flame retardant in compliance with IEC 60332-1.

DIMENSIONAL & MECHANICAL DATA

Control Cable

Nominal Cross Sectional Area	Maximum Diameter of Wire	Nominal Thickness		Approximately		Minimum Bending Radius	Standard Delivery Length *)
		Insulation	Outer Sheath	Overall Diameter	Cable Weight		
mm ²	mm	mm	mm	mm	Kg/Km	mm	m
5 x 0.75	0.20	0.6	0.9	8.1	98	57	2000
5 x 1	0.20	0.6	0.9	8.5	112	59	2000
5 x 1.5	0.25	0.7	1.1	10.1	164	71	2000
5 x 2.5	0.25	0.8	1.2	12.2	246	85	1000
5 x 4	0.30	0.8	1.2	13.5	334	95	1000
5 x 6	0.30	0.8	1.4	15.4	460	108	1000
5 x 10	0.40	1.0	1.6	19.7	767	138	500
7 x 0.75	0.20	0.6	1.0	9.1	125	63	2000
7 x 1	0.20	0.6	1.0	9.5	144	66	2000
7 x 1.5	0.25	0.7	1.2	11.3	203	79	2000
7 x 2.5	0.25	0.8	1.3	13.6	314	94	1000
10 x 0.75	0.20	0.6	1.1	11.7	183	81	2000
10 x 1	0.20	0.6	1.1	12.2	211	85	2000
10 x 1.5	0.25	0.7	1.3	14.5	305	106	1000
10 x 2.5	0.25	0.8	1.5	17.6	465	122	1000
12 x 0.75	0.20	0.6	1.1	12.0	208	84	1000
12 x 1	0.20	0.6	1.2	12.8	247	89	1000
12 x 1.5	0.25	0.7	1.3	14.9	349	104	1000
12 x 2.5	0.25	0.8	1.5	18.1	535	126	1000

*) Standard delivery length : 100m in coil and > 100m in drum

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
5 x 0.75	26.0	11	6	0.09
5 x 1.0	19.5	10	10	0.12
5 x 1.5	13.3	10	15	0.17
5 x 2.5	7.98	9	20	0.29
5 x 4	4.95	7	26	0.46
5 x 6	3.30	6	33	0.69
5 x 10	1.91	6	45	1.16
7 x 0.75	26.0	11	6	0.09
7 x 1.0	19.5	10	9	0.12
7 x 1.5	13.3	9	10	0.17
7 x 2.5	7.98	7	16	0.29
10 x 0.75	26.0	11	6	0.09
10 x 1.0	19.5	10	8	0.12
10 x 1.5	13.3	9	9	0.17
10 x 2.5	7.98	7	13	0.29
12 x 0.75	26.0	11	6	0.09
12 x 1.0	19.5	10	8	0.12
12 x 1.5	13.3	9	9	0.17
12 x 2.5	7.98	7	13	0.29



Cu/PVC/TCWB/PVC (LiYCY) 300/500 Volt

Manufacturing Spec. / IEC 60227.7

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED, BRAIDED WITH TINNED COPPER WIRE SHIELDED AND PVC SHEATHED CABLE

Applications : Power cord or internal wiring with low mechanical stress for electrical equipment, machineries, luminaires and other portable appliances used in dry indoor premises. Signal and control cables used for connection in electronic control technology, data transmission for voice frequency. Process control and instrumentation, The screening protects the cable against external electrical interference (EMI Protection)

DIMENSIONAL & MECHANICAL DATA

2, 3, 4, 5 Cores

Number Of Core	Conductor			Thickness		Approximately		Bending Radius	Standard Length *)
	Nominal Area	Maximum Diameter Wire	Diameter	Insulation	Outer Sheath	Diameter	Weight Of Cable		
	mm ²	mm	mm	mm	mm	mm	Kg/Km	mm	m
2	0.5	0.20	0.88	0.6	0.8	6.4	71	64	1000
2	0.75	0.20	1.13	0.6	0.8	6.9	83	69	1000
2	1	0.20	1.26	0.6	0.8	7.1	92	71	1000
2	1.5	0.25	1.53	0.7	0.9	8.3	112	83	1000
2	2.5	0.25	2.00	0.8	0.9	9.6	167	96	1000
3	0.5	0.20	0.88	0.6	0.8	6.7	74	67	1000
3	0.75	0.20	1.13	0.6	0.8	7.2	88	72	1000
3	1	0.20	1.26	0.6	0.9	7.7	102	77	1000
3	1.5	0.25	1.53	0.7	0.9	8.7	119	87	1000
3	2.5	0.25	2.00	0.8	1.0	10.4	191	104	1000
4	0.5	0.20	0.88	0.6	0.8	7.3	86	73	1000
4	0.75	0.20	1.13	0.6	0.9	8.0	106	80	1000
4	1	0.20	1.26	0.6	0.9	8.4	120	84	1000
4	1.5	0.25	1.53	0.7	0.9	9.5	157	95	1000
4	2.5	0.25	2.00	0.8	1.1	11.5	233	115	1000
5	0.5	0.20	0.88	0.6	0.9	8.1	103	81	1000
5	0.75	0.20	1.13	0.6	0.9	8.7	124	87	1000
5	1	0.20	1.26	0.6	1.0	9.3	145	93	1000
5	1.5	0.25	1.53	0.7	1.1	10.7	195	107	1000
5	2.5	0.25	2.00	0.8	1.2	12.9	292	129	1000

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
0.5	39.0	13	4	0.05
0.75	26.0	11	6	0.08
1	19.5	10	10	0.10
1.5	13.3	10	15	0.16
2.5	7.98	9	20	0.26


Core identification :

- 2 cores by colours : Blue, Brown;
- 3 cores by colours : Green-Yellow, Blue, Brown ;
- 4 cores by colours : Green-Yellow, Blue, Black, Brown ;
- 5 cores by colours : Green-Yellow, Blue, Brown, Black, Gray.

Colour of Outer sheath : Gray colour

Other size, core identification and packing length are available upon request

Note: This only general information. For other specific requirement, please contact our marketing





SUPREME CABLE

FLEXIBLE CABLE

Cu/PVC/TCWB/PVC (LiYCY) 300/500 Volt

Manufacturing Spec. / IEC 60227.7

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED, BRAIDED
WITH TINNED COPPER WIRE SHIELDED AND PVC SHEATHED CABLE

Applications : Power cord or internal wiring with low mechanical stress for electrical equipment, machineries, luminaires and other portable appliances used in dry indoor premises. Signal and control cables used for connection in electronic control technology, data transmission for voice frequency. Process control and instrumentation, The screening protects the cable against external electrical interference (EMI Protection)

DIMENSIONAL & MECHANICAL DATA

Control Cable

Number Of Core	Conductor			Thickness		Approximately		Bending Radius	Standard Length *)
	Nominal Area	Maximum Diameter Wire	Diameter	Insulation	Outer Sheath	Diameter	Weight Of Cable		
pcs	mm ²	mm	mm	mm	mm	mm	Kg/Km	mm	m
6	0.5	0.20	0.88	0.6	0.9	8.7	119	87	1000
6	0.75	0.20	1.13	0.6	1.0	9.6	148	96	1000
6	1	0.20	1.26	0.6	1.0	10.0	167	100	1000
6	1.5	0.25	1.53	0.7	1.1	11.6	226	116	1000
6	2.5	0.25	2.00	0.8	1.3	14.1	343	141	1000
7	0.5	0.20	0.88	0.6	0.9	8.7	125	87	1000
7	0.75	0.20	1.13	0.6	1.0	9.6	155	96	1000
7	1	0.20	1.26	0.6	1.0	10.0	176	100	1000
7	1.5	0.25	1.53	0.7	1.1	11.7	246	117	1000
7	2.5	0.25	2.00	0.8	1.3	14.1	366	141	1000
8	0.5	0.20	0.88	0.6	1.0	9.5	144	95	1000
8	0.75	0.20	1.13	0.6	1.0	10.3	180	103	1000
8	1	0.20	1.26	0.6	1.1	11.0	211	110	1000
8	1.5	0.25	1.53	0.7	1.2	12.8	289	128	1000
8	2.5	0.25	2.00	0.8	1.4	15.4	427	154	1000
10	0.5	0.20	0.88	0.6	1.1	11.2	184	112	1000
10	0.75	0.20	1.13	0.6	1.2	12.3	230	123	1000
10	1	0.20	1.26	0.6	1.2	12.9	262	129	1000
10	1.5	0.25	1.53	0.7	1.4	15.2	372	152	1000
10	2.5	0.25	2.00	0.8	1.5	18.1	540	181	1000

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
6 x 0.5	39.0	13	3	0.05
6 x 0.75	26.0	11	5	0.08
6 x 1	19.5	10	9	0.10
6 x 1.5	13.3	10	14	0.16
6 x 2.5	7.98	9	19	0.26
7 x 0.5	39.0	13	3	0.05
7 x 0.75	26.0	11	5	0.08
7 x 1	19.5	10	9	0.10
7 x 1.5	13.3	10	14	0.16
7 x 2.5	7.98	9	19	0.26
8 x 0.5	39.0	13	3	0.05
8 x 0.75	26.0	11	5	0.08
8 x 1	19.5	10	8	0.10
8 x 1.5	13.3	10	12	0.16
8 x 2.5	7.98	9	16	0.26
10 x 0.5	39.0	13	3	0.05
10 x 0.75	26.0	11	4	0.08
10 x 1	19.5	10	7	0.10
10 x 1.5	13.3	10	11	0.16
10 x 2.5	7.98	9	15	0.26

Other size, core identification and packing length are available upon request

Note: This only general information. For other specific requirement, please contact our marketing





SUPREME CABLE

FLEXIBLE CABLE

Cu/PVC/TCWB/PVC (LiYCY) 300/500 Volt

Manufacturing Spec. / IEC 60227.7

FLEXIBLE COPPER CONDUCTOR, PVC INSULATED, BRAIDED
WITH TINNED COPPER WIRE SHIELDED AND PVC SHEATHED CABLE

Applications : Power cord or internal wiring with low mechanical stress for electrical equipment, machineries, luminaires and other portable appliances used in dry indoor premises. Signal and control cables used for connection in electronic control technology, data transmission for voice frequency. Process control and instrumentation, The screening protects the cable against external electrical interference (EMI Protection)

DIMENSIONAL & MECHANICAL DATA

Control Cable

Number Of Core	Conductor			Thickness		Approximately		Bending Radius	Standard Length *)
	Nominal Area	Maximum Diameter Wire	Diameter	Insulation	Outer Sheath	Diameter	Weight Of Cable		
pcs	mm ²	mm	mm	mm	mm	mm	Kg/Km	mm	m
12	0.5	0.20	0.88	0.6	1.1	11.6	216	116	1000
12	0.75	0.20	1.13	0.6	1.2	12.8	269	128	1000
12	1	0.20	1.26	0.6	1.2	13.3	308	133	1000
12	1.5	0.25	1.53	0.7	1.4	15.7	417	157	1000
12	2.5	0.25	2.00	0.8	1.6	18.9	614	189	1000
14	0.5	0.20	0.88	0.6	1.2	12.3	234	123	1000
14	0.75	0.20	1.13	0.6	1.2	13.4	287	134	1000
14	1	0.20	1.26	0.6	1.3	14.2	335	142	1000
14	1.5	0.25	1.53	0.7	1.4	16.4	457	164	1000
14	2.5	0.25	2.00	0.8	1.7	20.0	688	200	1000
15	0.5	0.20	0.88	0.6	1.2	12.9	253	129	1000
15	0.75	0.20	1.13	0.6	1.3	14.3	317	143	1000
15	1	0.20	1.26	0.6	1.3	14.9	362	149	1000
15	1.5	0.25	1.53	0.7	1.5	17.5	501	175	1000
15	2.5	0.25	2.00	0.8	1.7	21.1	745	211	1000
16	0.5	0.20	0.88	0.6	1.2	12.9	263	129	1000
16	0.75	0.20	1.13	0.6	1.3	14.3	330	143	1000
16	1	0.20	1.26	0.6	1.3	14.9	376	149	1000
16	1.5	0.25	1.53	0.7	1.5	17.5	519	175	1000
16	2.5	0.25	2.00	0.8	1.7	21.1	770	211	1000

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
12 x 0.5	39.0	13	3	0.05
12 x 0.75	26.0	11	4	0.08
12 x 1	19.5	10	7	0.10
12 x 1.5	13.3	10	11	0.16
12 x 2.5	7.98	9	15	0.26
14 x 0.5	39.0	13	3	0.05
14 x 0.75	26.0	11	4	0.08
14 x 1	19.5	10	7	0.10
14 x 1.5	13.3	10	10	0.16
14 x 2.5	7.98	9	14	0.26
15 x 0.5	39.0	13	3	0.05
15 x 0.75	26.0	11	4	0.08
15 x 1	19.5	10	7	0.10
15 x 1.5	13.3	10	10	0.16
15 x 2.5	7.98	9	14	0.26
16 x 0.5	39.0	13	3	0.05
16 x 0.75	26.0	11	4	0.08
16 x 1	19.5	10	7	0.10
16 x 1.5	13.3	10	10	0.16
16 x 2.5	7.98	9	13	0.26

Other size, core identification and packing length are available upon request

Note: This only general information. For other specific requirement, please contact our marketing



Cu/PVC/TCWB/PVC (LiYCY) 300/500 Volt

Manufacturing Spec. / IEC 60227.7

**FLEXIBLE COPPER CONDUCTOR, PVC INSULATED, BRAIDED
WITH TINNED COPPER WIRE SHIELDED AND PVC SHEATHED CABLE**

Applications : Power cord or internal wiring with low mechanical stress for electrical equipment, machineries, luminaires and other portable appliances used in dry indoor premises. Signal and control cables used for connection in electronic control technology, data transmission for voice frequency. Process control and instrumentation, The screening protects the cable against external electrical interference (EMI Protection)

DIMENSIONAL & MECHANICAL DATA

Control Cable

Number Of Core	Conductor			Thickness		Approximately		Bending Radius	Standard Length *)
	Nominal Area	Maximum Diameter Wire	Diameter	Insulation	Outer Sheath	Diameter	Weight Of Cable		
	mm ²	mm	mm	mm	mm	mm	Kg/Km	mm	m
19	0.5	0.20	0.88	0.6	1.3	13.7	293	137	1000
19	0.75	0.20	1.13	0.6	1.3	15.0	362	150	1000
19	1	0.20	1.26	0.6	1.4	15.8	424	158	1000
19	1.5	0.25	1.53	0.7	1.6	18.6	587	186	1000
19	2.5	0.25	2.00	0.8	1.8	22.3	876	223	1000
21	0.5	0.20	0.88	0.6	1.4	15.2	335	152	1000
21	0.75	0.20	1.13	0.6	1.5	16.8	432	168	1000
21	1	0.20	1.26	0.6	1.6	17.7	489	177	1000
21	1.5	0.25	1.53	0.7	1.8	20.7	675	207	1000
21	2.5	0.25	2.00	0.8	2.1	25.1	1.016	251	1000
24	0.5	0.20	0.88	0.6	1.4	16.0	376	160	1000
24	0.75	0.20	1.13	0.6	1.6	17.9	475	179	1000
24	1	0.20	1.26	0.6	1.6	18.7	550	187	1000
24	1.5	0.25	1.53	0.7	1.8	21.9	755	219	1000
24	2.5	0.25	2.00	0.8	2.1	26.5	1.136	265	1000
27	0.5	0.20	0.88	0.6	1.4	16.3	401	163	1000
27	0.75	0.20	1.13	0.6	1.5	18.0	505	180	1000
27	1	0.20	1.26	0.6	1.6	19.1	591	191	1000
27	1.5	0.25	1.53	0.7	1.8	22.3	822	223	1000
27	2.5	0.25	2.00	0.8	2.1	27.2	1267	272	1000

ELECTRICAL DATA

Nominal Cross Sectional Area	Resistance at 20°C		Current Carrying Capacity in Air at 30°C Max	Short Circuit Current of Conductor at 1.0 sec Max
	DC Conductor Max	Insulation Min		
mm ²	Ω/Km	MΩ.km	A	kA
19 x 0.5	39.0	13	2.5	0.05
19 x 0.75	26.0	11	4	0.08
19 x 1	19.5	10	6	0.10
19 x 1.5	13.3	10	9	0.16
19 x 2.5	7.98	9	13	0.26
21 x 0.5	39.0	13	2.5	0.05
21 x 0.75	26.0	11	4	0.08
21 x 1	19.5	10	6	0.10
21 x 1.5	13.3	10	8	0.16
21 x 2.5	7.98	9	12	0.26
24 x 0.5	39.0	13	2.5	0.05
24 x 0.75	26.0	11	4	0.08
24 x 1	19.5	10	6	0.10
24 x 1.5	13.3	10	8	0.16
24 x 2.5	7.98	9	12	0.26
27 x 0.5	39.0	13	2.5	0.05
27 x 0.75	26.0	11	4	0.08
27 x 1	19.5	10	6	0.10
27 x 1.5	13.3	10	8	0.16
27 x 2.5	7.98	9	12	0.26

Other size, core identification and packing length are available upon request

Note: This only general information. For other specific requirement, please contact our marketing





SUPREME CABLE

FLEXIBLE CABLE

CONVERSION TABLE

Nominal Cross Sectional Area			Wire Gauge			
mm ²	Inc ²	Circular Mils (CM)	Equivalent Metric CSA	AWG	BWG	SWG
	0.0005	644	0.325	22	-	-
	0.0006	487	0.397	-	22	22
	0.0006	821	0.416	21	-	-
0.50	0.0008	987	-	-	-	-
	0.0008	1,021	0.517	20	-	-
	0.0008	1,025	0.519	-	21	21
	0.0009	1,198	0.607	-	20	-
	0.0010	1,289	0.653	19	-	-
	0.0010	1,297	0.657	-	-	20
	0.0013	1,601	0.811	-	-	19
0.75	0.0012	1,481	-	-	-	-
	0.0013	1,625	0.823	18	-	-
	0.0014	1,765	0.894	-	19	-
1.0	0.0016	1,974	-	-	-	-
	0.0016	2,053	1.040	17	-	-
	0.0016	2,304	1.167	-	-	18
	0.0019	2,402	1.217	-	18	-
	0.0020	2,584	1.309	16	-	-
1.5	0.0023	2,961	-	-	-	-
	0.0025	3,137	1.589	-	-	17
	0.0026	3,257	1.650	15	-	-
	0.0026	3,366	1.705	-	17	-
	0.0032	4,096	2.075	-	-	16
	0.0032	4,108	2.081	14	-	-
	0.0033	4,226	2.141	-	16	-
2.5	0.0039	4,935	-	-	-	-
	0.0040	5,180	2.624	13	-	-
	0.0040	5,186	2.627	-	15	15
	0.0050	6,402	3.243	-	-	14
	0.0051	6,532	3.309	12	-	-
	0.0054	6,891	3.491	-	14	-
4	0.0062	7,896	-	-	-	-
	0.0065	8,236	4.172	11	-	-
	0.0066	8,466	4.269	-	-	13
	0.0071	9,072	4.573	-	13	-
	0.0082	10,387	5.262	10	-	-
	0.0085	10,819	5.481	-	-	12
	0.0093	11,883	6.020	-	12	-
6	0.0093	11,844	-	-	-	-
	0.0103	13,092	6.632	9	-	-
	0.0106	13,459	6.816	-	-	11
	0.0113	14,404	7.297	-	11	-
	0.0129	16,388	8.302	-	-	10
	0.0130	16,518	8.368	8	-	-
	0.0141	17,959	9.098	-	10	-
10	0.0155	19,740	-	-	-	-
	0.0163	20,766	10.520	-	-	9
	0.0164	20,826	10.550	7	-	-
	0.0172	21,911	11.100	-	9	-
	0.0201	25,603	12.970	-	-	8
	0.0206	26,254	13.300	6	-	-
	0.0214	27,241	13.800	-	8	-
	0.0243	30,992	15.700	-	-	7
16	0.0248	31,584	-	-	-	-
	0.0255	32,413	16.420	-	7	-
	0.0260	33,104	16.770	5	-	-

Nominal Cross Sectional Area			Wire Gauge			
mm ²	Inc ²	Circular Mils (CM)	Equivalent Metric CSA	AWG	BWG	SWG
	0.0290	36,874	18.68	-	-	6
	0.0324	41,217	20.88	-	6	-
	0.0326	41,750	21.15	4	-	-
	0.0353	44,948	22.77	-	-	5
	0.0380	48,402	24.52	-	5	-
25	0.0388	49,350	-	-	-	-
	0.0413	52,627	26.66	3	-	-
	0.0423	53,831	27.27	-	-	4
	0.0445	56,654	28.70	-	4	-
	0.0499	63,523	32.18	-	-	3
	0.0521	66,386	33.63	2	-	-
	0.0527	67,096	33.99	-	3	-
35	0.0543	69,090	-	-	-	-
	0.0598	76,196	28.60	-	-	2
	0.0633	80,677	40.87	-	2	-
	0.0657	83,717	42.41	1	-	-
	0.0707	90,014	45.60	-	1	1
50	0.0775	98,700	-	-	-	-
	0.0824	404,997	53.19	-	-	1/0
	0.0829	105,589	53.49	1/0	-	-
	0.0908	115,637	58.58	-	1/0	-
	0.0951	121,125	61.36	-	-	2/0
	0.1045	133,087	67.42	2/0	-	-
70	0.1085	138,180	-	-	-	-
	0.1087	138,417	70.12	-	-	3/0
	0.1134	144,438	73.17	-	2/0	-
	0.1257	160,032	81.07	-	-	4/0
	0.1318	167,849	85.03	3/0	-	-
	0.1419	180,660	91.52	-	3/0	-
	0.1466	186,661	94.56	-	-	5/0
95	0.1473	187,530	-	-	-	-
	0.1616	206,086	104.40	-	4/0	-
	0.1691	211,613	107.20	4/0	-	-
	0.1860	215,363	109.10	-	-	6/0
120	0.1860	236,880	-	-	-	-
	0.1963	249,987	126.64	-	-	-
	0.1964	250,106	126.70	-	5/0	7/0
	0.2091	266,332	134.92	5/0	-	-
150	0.2325	296,100	-	-	-	-
	0.2356	300,048	152.00	-	-	-
	0.2642	336,488	170.46	6/0	-	-
185	0.2868	365,190	-	-	-	-
	0.3142	400,150	202.71	-	-	-
240	0.3720	473,760	-	-	-	-
	0.3927	500,113	253.35	-	-	-
300	0.4650	592,200	-	-	-	-
	0.4712	600,096	304.00	-	-	-
	0.5498	700,198	354.71	-	-	-
400	0.6200	789,600	-	-	-	-
	0.6283	800,161	405.35	-	-	-
500	0.7750	987,000	-	-	-	-
	0.7854	1,000,246	506.71	-	-	-
625	0.9688	1,233,750	-	-	-	-
630	0.9765	1,243,620	-	-	-	-
800	1.2400	1,597,200	-	-	-	-
1,000	1.5500	1,974,000	-	-	-	-

AWG : American Wire Gauge

BWG : Birmingham Wire Gauge

SWG : British Standard Wire Gauge