

HIKVISION®



KATALOG RETAIL **2024**

www.hikvision.com

Hikvision Lampu Kamera

Smart Hybrid Light



NEW

DS-2CE18D0T-LFS

- 2 MP, 2.8 mm, 3.6 mm and 6mm fixed focal lens
- Smart Hybrid light
- High quality audio with audio over coaxial cable, built-in mic
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



DS-2CE16D0T-LPFS

DS-2CE16D0T-LFS

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE76D0T-LPFS

DS-2CE76D0T-LMFS

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu (Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE16D0T-EXLPF

DS-2CE16D0T-EXLF

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE76D0T-EXLPF

DS-2CE76D0T-EXLMF

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE17D0T-IT1F

DS-2CE17D0T-IT3F

DS-2CE17D0T-IT5F

- 2MP CMOS Sensor, EXIR 30m IR,
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP67, 2.8/3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR
3 : EXIR 40m IR
5 : EXIR 80m IR



DS-2CE56D0T-IT1F

DS-2CE56D0T-IT3F

- HD1080p, 2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR,
- Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR
3 : EXIR 40m IR
5 : EXIR 80m IR



DS-2CE16D0T-ITF

- 2MP CMOS Sensor, EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12VDC,
- Smart IR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output



DS-2CE76D0T-ITMF

- 2MP CMOS Sensor, EXIR 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC,
- Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output

ANALOG 3K



DS-2CE16K0T-LPFS

DS-2CE16K0T-LFS

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE76K0T-LPFS

DS-2CE76K0T-LFS

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu(Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



DS-2CE16K0T-EXLPF

DS-2CE16K0T-EXLF

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE76K0T-EXLPF

DS-2CE76K0T-EXLMF

- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



DS-2CE19H0T-AIT3ZF

DS-2CE19H8T-AIT3ZF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Auto Focus ,
- Outdoor Bullet, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : 30m IR
3 : 40m IR
8 : Lux 0.003



DS-2CE57H0T-VPITF

DS-2CE57H8T-VPITF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, 0.003 Lux/F1.2, 12 VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (x) : 0 : Lux 0.01
8 : Lux 0.003



DS-2CE5AH8T-AVPIT3ZF

DS-2CE59H8T-AVPIT3ZF

DS-2CE56H8T-AITZF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 60m IR, Auto Focus ,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- V : Outdoor Vandal Proof Dome



DS-2CE16H8T-ITF

DS-2CE16H8T-IT(x)F

DS-2CE16H0T-ITPF(s)

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.003 Lux/F1.2, 12VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : 30m IR
3 : 40m IR
5 : 80m IR



DS-2CE76H0T-ITPF(s)

DS-2CE76H0T-ITMF

DS-2CE76H8T-ITMF

- 5MP@20fps, 4MP@25fps(P)/30fps(N), EXIR, up to 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic, Audio up Coaxial(Only TVI),
- HOT : 0.01 Lux
H8T : 0.003 Lux

2MP



NEW

DS-2CE10DF0T-LPFS

DS-2CE10DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Bullet 0.001Lux/F1.0 20m IR+20m White Light
- 3D DNR 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- 24H ColorSmart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE12DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6/6mm Lens 24H Color
- Outdoor smart hybrid light Bullet 0.001Lux/F1.0 40m IR+40m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- Smart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE70DF0T-LPFS

DS-2CE70DF0T-LMFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Turret 0.001Lux/F1.0 20m IR+20m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI)
- OSD Menu(Up the Coax)
- IP67
- 24H Color Smart Lighting With Acusense DV Support TVI/AHD/CVI/CVBS video signal output



DS-2CE72DF0T-LFS

- 2M CMOS Sensor, 2.8/3.6mm Lens
- Outdoor smart hybrid light Turret 0.001Lux/F1.0 40m IR+40m White Light
- 3D DNR
- 12 VDC
- Built-in Mic Audio up Coaxial(Only TVI) OSD Menu(Up the Coax)
- IP67
- 24H Color Smart Lighting With Acusense DVR Support TVI/AHD/CVI/CVBS video signal output



NEW

DS-2CE10KF0T-L(P)FS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



NEW

DS-2CE12KF0T-LFS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



24/7

Gambar Berwarna

5MP



NEW

DS-2CE70KF0T-LM(P)FS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



NEW

DS-2CE72KF0T-LFS

- 3K(5MP 16:9), 2.8 mm, 3.6 mm fixed focal lens
- Smart Hybrid light with ColorVu
- High quality audio with audio over coaxial cable, built-in mic
- Super Confocal F1.0 Lens
- 4 in 1(TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)



DS-2CE10DF3T-(P)F(S)

- 2M BSI CMOS Sensor,
- Outdoor mini Bullet, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 20M, 3D DNR, DC 12V, OSD Menu (Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color, Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic, Audio up Coaxial (Only TVI)



DS-2CE12DF3T-F(S)

- 2M BSI CMOS Sensor,
- Outdoor Bullet, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 40M, 3D DNR, DC 12V, OSD Menu (Up the Coax), 130dB True WDR, IP67, 2.8/3.6/6mm Lens,
- 24H Color, Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic, Audio up Coaxial (Only TVI),



DS-2CE72DF3T-FS

- 2M BSI CMOS Sensor,
- Outdoor Turret, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 40M, 3D DNR, DC 12V, OSD Menu (Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color, Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic, Audio up Coaxial (Only TVI),



DS-2CE70DF3T-(P)F(S)

- 2M BSI CMOS Sensor,
- Indoor Turret, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 20M, 3D DNR, DC 12V, OSD Menu (Up the Coax), 130dB True WDR, 2.8/3.6mm Lens,
- 24H Color, Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic, Audio up Coaxial (Only TVI),

4K IN FULL COLOUR 24/7 WITH LIGHT & SOUND DETERRENCE

Pro Series 8 MP

with Live Guard & ColorVu Technology



DS-2CE16U1T-IT(x)F

DS-2CE16U7T-IT(3)F

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N),
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic
- U1T : 0.01 Lux, U7T : 0.003 Lux
- (X) : 1 : 30m IR, 3 : 60m IR, 5 : 80m IR



DS-2CE19U1T-IT3ZF

DS-2CE19U1T-AIT3ZF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 80m IR, Auto Focus,
- Outdoor Bullet, ICR, 0.01 Lux/F1.2, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) : 12VDC/AC24V



DS-2CE56U1T-ITZF

DS-2CE56U1T-AITZF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 60m IR, Auto Focus,
- Indoor Dome, ICR, 0.01 Lux/F1.2, 12 VDC/AC24V, Smart IR, DNR, OSD Menu(Up the Coax), 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) : 12VDC/AC24V



DS-2CE57U1T-VPITF

DS-2CE57U7T-VPITF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP67, 3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- U1T : 0.01 Lux
- U7T : 0.003 Lux



DS-2CE59U1T-(A)VPIT3ZFP

DS-2CE59U7T-AVPIT3ZF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Indoor EXIR Turret, ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux
- U7T : 0.003 Lux



DS-2CE5AU1T-AVPIT3ZF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 60m IR, Auto Focus,
- Outdoor Vandal Proof Dome, ICR, 0.01 Lux/F1.2, 12 VDC/AC24V, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (A) : 12VDC/AC24V



DS-2CE76U1T-IT(P)F

DS-2CE76U7T-ITMF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Indoor EXIR Turret, ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux, U7T : 0.003 Lux



DS-2CE78U1T-IT(X)F

DS-2CE78U7T-IT3F

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- U1T : 0.01 Lux, U7T : 0.003 Lux
- (X) : 1 : 30m IR, 3 : 60m IR



DS-2CE79U1T-IT3ZF

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 60m IR, Auto Focus,
- Outdoor Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output

TURBO HD PTZ



DS-2AE4225TI-D

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:25x, Digital Zoom:16X,
- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,
- Up the Coax,100mIR,DC12V



DS-2AE4215TI-D

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:15x,
- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,
- Up the Coax,100m IR,DC12V



DS-2AE4225T-D

DS-2AE4225T-D3

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6,
- Optical Zoom:25x, Digital Zoom:16X,
- Up the Coax,DC12V



DS-2AE4215T-D3

- 1/3" CMOS, 1920x1280:30fps, 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:15x, Focus:4.0-60mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -5°~90°(Auto Flip),
- Pan Speed: 0.1° ~160°/s, Tilt Speed: 0.1° ~120°/s,
- Up the Coax, 24VAC

COMING
SOON

HIKVISION®

Turbo HD 8.0

Wider vision, interactive connection

- POINT 01 – **TVI Two-way Audio**
Interactive communication with crystal-clear audio effect
- POINT 02 – **Compact Dual-lens Stitching**
Perfect 180-degree stitched images to ensure seamless visuals
- POINT 03 – **Upgraded Intelligence**
Improved night vision experience via Smart Hybrid Light; smarter video searching via AcuSearch

Two-way Audio

Smart Hybrid Light

Dual-lens Stitching

AcuSearch



www.hikvision.com
support@hikvision.com



TURBO 5^{HD}.0

More Than What You See



IDS-7204HQHI-M1/E

IDS-7208HQHI-M1/E

IDS-7216HQHI-M1/E

- Full-channel motion detection 2.0 or 2/4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, H.265/H.265+ compression,
- 2-ch IP video input(up to 24-ch IP), 1 SATA interface
- CH01-04:1920×1080P @15 fps, 4MP Lite@15fps/ch, 260 1U case



IDS-7204HUHI-M1/E

IDS-7208HUHI-M1/E

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 8-ch HDTV1 coaxial video&audio input, 1-ch RCA audio input,
- 4-ch IP video input(up to 16-ch IP), 1 SATA interface,
- H.265/H.265+ compression,
- 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 260 1U case



IDS-7204HQHI-M1/S

IDS-7208HQHI-M1/S

IDS-7208HQHI-M2/S

IDS-7216HQHI-M1/S

IDS-7216HQHI-M2/S

IDS-7232HQHI-M2/S

- Full-channel motion detection 2.0 or 2/4-ch false alarm filter,
- Up to 32-ch Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 32-ch video&1-ch audio input, H.265/H.265+ compression, 1/2 SATA interface,
- 3MP @ 15fps, 1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output



IDS-7204HUHI-M1/S

IDS-7208HUHI-M1/S

IDS-7204HUHI-M2/S

IDS-7208HUHI-M2/S

IDS-7216HUHI-M2/S

- Full-channel motion detection or 4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, 1/2 SATA interface, H.265/H.265+ compression,
- 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, support CVBS output, stand alone 1U case



IDS-7204HUHI-M1/S

IDS-7208HUHI-M1/S

IDS-7208HUHI-M1/S

IDS-7208HUHI-M2/S

IDS-7216HUHI-M2/S

- Full-channel motion detection or 4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, 1/2 SATA interface, H.265/H.265+ compression,
- 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, support CVBS output, stand alone 1U case



IDS-7204HTHI-M1/S

IDS-7204HTHI-M2/S

IDS-7208HTHI-M2/S

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 1/2 SATA interface, H.265/H.265+ compression,
- 8 MP@12fps, 5 MP@20fps, 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), support CVBS output, standalone 1U case



IDS-7316HQHI-M4/S

IDS-7332HQHI-M4/S

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 32 Turbo HD/CVI / AHD / CVBS interface input,
- Up to 32-ch video&4-ch audio input, 4/16-ch IP video input(up to 48-ch IP), 2 RJ45 10M/100M/1000M self-adaptive Ethernet interface
- H.264/H.264+/H.265+/H.265 video compression, 4 SATA interface,
- 1920×1080P @15 fps, 4MP Lite @ 15fps/ch, Extended transmission distance over coax cable, 4K UHD output, 1.5U 19" case



IDS-7316HUHI-M4/S

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- 16-ch video&4-ch audio input, 18-ch IP video input(up to 34-ch IP),
- H.264/H.264+/H.265+/H.265 video compression, 4 SATA interfaces,
- 8MP: 8 fps/ch, 5MP: 12 fps/ch, 4MP: 15 fps/ch, Extended transmission distance over coax cable, 4K UHD output, alarm I/O: 16/4, 1.5U 19" case

Teknologi smart

HYBRID LIGHT

Seri Ekonomis ColorVu

Alarm lampu hanya menyala tepat saat dibutuhkan



Smart Mode

White Light Mode

IR Mode



Iluminasi Cahaya Hybrid
yang Fleksibel



Target Kendaraan dan Manusia
dengan Warna Asli



Lampu Peringatan
kepada Penyusup



NEW

DS-2CD1021G0-I

DS-2CD1021G0-IU

- 1/3" Progressive CMOS ICR
- 1920 × 1080: 25fps(P)/30fps(N)
- H.265+/H.265/H.264+&H.264
- DWDR, 3D DNR, BLC
- IR range: up to 30m
- DC12V & PoE
- IU :Built-in microphone



NEW

DS-2CD1121G0-I

- 1/3" Progressive CMOS ICR
- 1920 × 1080: 25fps(P)/30fps(N)
- H.265+/H.265/H.264+&H.264
- DWDR, 3D DNR, BLC
- IR range: up to 30m
- DC12V & PoE



NEW

DS-2CD1321G0-I

DS-2CD1321G0-IU

- 1/3" Progressive CMOS ICR
- 1920 × 1080: 25fps(P)/30fps(N)
- H.265+/H.265/H.264+&H.264
- DWDR, 3D DNR, BLC
- IR range: up to 30m
- DC12V & PoE
- IU :Built-in microphone

Gunakan Smart Hybrid Light Kamera!



**3 Mode Pencahayaan
Tambahan**



NEW

DS-2CD1T23G2-LIUF

DS-2CD1T43G2-LIUF

- 1/3" Progressive CMOS, ICR
- IT23:1920 × 1080: 25fps(P)/30fps(N)
- IT43:2560 × 1440: 20fps(P)/(N),
- H.265+/H.265/H.264+&H.264,
- DWDR, 3D DNR, BLC,
- IR or white light range: up to 50m,
- Built-in microphone
- DC12V & PoE, Support mobile monitoring via Hik-Connect
- (F): SD Card Slot (up to 256GB)



NEW

DS-2CD1T63G2-LIUF

DS-2CD1T83G2-LIUF

- 1/3" Progressive CMOS, ICR
- 3200 × 1800: 20fps(P/N),
- 3840 × 2160: 12.5fps(P)/15fps(N)
- H.265+/H.265/H.264+&H.264,
- DWDR, 3D DNR, BLC,
- IR or white light range: up to 50m,
- Built-in microphone
- DC12V & PoE, Support mobile monitoring via Hik-Connect



DS-2CD1043G2-LIU

DS-2CD1023G2-LIU

DS-2CD1023G2-LIUF

- 1/3" Progressive CMOS, ICR,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- IR or white light range: up to 30m,
- Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- (F): SD Card Slot (up to 256GB)



DS-2CD1143G2-LIU

DS-2CD1123G2-LIU

DS-2CD1123G2-LIUF

- 1/3" Progressive CMOS, ICR,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- IR or white light range: up to 30m,
- Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- (F): SD Card Slot (up to 256GB)



DS-2CD1323G2-LIU

DS-2CD1323G2-LIUF

- 1/3" Progressive CMOS, ICR, 1920x1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- IR or white light range: up to 30m,
- Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- (F): SD Card Slot (up to 256GB)

ColorVu LITE

Ekonomis & Berwarna

- F1.0 Super Aperture
- Sensor Canggih
- 30m Warm Light



DS-2CD1027G2H-LIU

DS-2CD1027G2H-LIUF

DS-2CD1047G2H-LIU

DS-2CD1047G2H-LIUF

NEW

- 1/3" Progressive CMOS, ICR, H.265+/H.265/
- H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:
- 25fps(P)/30fps(N),
- IR or white light range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Build-in microphone & SD Card Slot (up to 512GB),



DS-2CD1327G2H-LIU

DS-2CD1327G2H-LIUF

DS-2CD1347G2H-LIU

DS-2CD1347G2H-LIUF

NEW

- 1/3" Progressive CMOS, ICR, H.265+/H.265/
- H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:
- 25fps(P)/30fps(N),
- IR or white light range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Build-in microphone & SD Card Slot (up to 512GB),



DS-2CD1127G2H-LIU

DS-2CD1127G2H-LIUF

DS-2CD1147G2H-LIU

DS-2CD1147G2H-LIUF

NEW

- 1/3" Progressive CMOS, ICR, H.265+/H.265/
- H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:
- 25fps(P)/30fps(N),
- IR or white light range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Build-in microphone & SD Card Slot (up to 512GB),



DS-2CD1T27G2H-LIU

DS-2CD1T27G2H-LIUF

DS-2CD1T47G2H-LIU

DS-2CD1T47G2H-LIUF

NEW

- 1/3" Progressive CMOS, ICR, H.265+/H.265/
- H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:
- 25fps(P)/30fps(N),
- IR or white light range: up to 50m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Build-in microphone & SD Card Slot (up to 512GB),

Easy IP 1.0 2MP



DS-2CD2421G0-I

- 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.028 Lux @ (F2.0, AGC ON), 0 lux with IR; 25Fps/30fps(1920x1080);
- VCA functions; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 10m; DC12V&PoE;
- Built-in mic&speaker; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service



DS-2CD2021G1-I

- 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC,
- Line crossing detection, Intrusion detection . IR range: up to 30m,
- Hik-Connect cloud service



DS-2CD2121G0-I

DS-2CD2121G0-IS

- 1/2.8" Progressive CMOS, ICR, 0lux with IR,
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC, Line crossing detection, Intrusion detection . IR range: up to 30m,
- Support on-board storage (SD card not included), Hik-Connect cloud service
- (S) : Audio/Alarm IO connectors



DS-2CD2321G0-I/NF

- 1/2.8" Progressive CMOS, ICR, 0lux with IR,
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC, Line crossing detection, Intrusion detection . IR range: up to 30m,
- Hik-Connect cloud service



DS-2CD2621G0-I

DS-2CD2621G0-IS

DS-2CD2621G0-IZ

DS-2CD2621G0-IZS

- 1/2.8" Progressive CMOS, ICR, 0lux with IR,
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC, Line crossing detection, Intrusion detection . IR: up to 30m,
- Support on-board card slot (SD card not included), Hik-Connect cloud service
- (S) : Audio/Alarm IO connectors
- (Z) : Motorized VF lens



DS-2CD2721G0-I

DS-2CD2721G0-IS

DS-2CD2721G0-IZ

DS-2CD2721G0-IZS

- 1/2.8" Progressive CMOS, ICR, 0lux with IR,
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC, Line crossing detection, Intrusion detection .IR: up to 30m,
- Support on-board card slot (SD card not included), Vandal-proof, Hik-Connect cloud service
- (S) : Audio/Alarm IO connectors
- (Z) : Motorized VF lens



DS-2CD2821G0

- 1/2.8" Progressive CMOS, ICR, Color: 0.005 Lux @ (F1.2, AGC ON),
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC,
- Support on-board card slot (SD card not included), Hik-Connect cloud service
- Audio/Alarm IO connectors.

NEW

**FOCUS
and
ACT**

AcuSense Technology



NEW

DS-2CD2023G2-LI

DS-2CD2023G2-LI2U

DS-2CD2043G2-LI

DS-2CD2043G2-LI2U

DS-2CD2063G2-LI

DS-2CD2063G2-LI2U

- 1/2.8" Progressive Scan CMOS;
6 MP : 20fps(3200x1800), 4MP :
25fps/30fps(2688x1520), 2MP : 25fps/30fps
(1920x1080);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;
- VCA functions; 3 streams;
- 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR,
up to 40m;
- DC12V&PoE; Built-in micro SD/SDHC/SDXC slot;
HIK-Connect cloud service
- 2U: Built-in Dual-Array Microphone



NEW

DS-2CD2123G2-LI

DS-2CD2123G2-LIS2U

DS-2CD2143G2-LI

DS-2CD2143G2-LIS2U

DS-2CD2163G2-LI

DS-2CD2163G2-LIS2U

- 1/2.8" Progressive Scan CMOS;
6 MP : 20fps(3200x1800), 4MP :
25fps/30fps(2688x1520), 2MP : 25fps/30fps
(1920x1080);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;
- VCA functions; 3 streams;
- 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up
to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect
cloud service

*S model: Audio/Alarm IO

*2U: Built-in Dual-Array Microphone



NEW

DS-2CD2323G2-LI

DS-2CD2323G2-LI2U

DS-2CD2343G2-LI

DS-2CD2343G2-LI2U

DS-2CD2363G2-LI

DS-2CD2363G2-LI2U

- 1/2.8" Progressive Scan CMOS;
6 MP : 20fps(3200x1800), 4MP :
25fps/30fps(2688x1520), 2MP : 25fps/30fps
(1920x1080);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;
- VCA functions; 3 streams;
- 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR,
up to 40m;
- DC12V&PoE; Built-in micro SD/SDHC/SDXC slot;
HIK-Connect cloud service
- * -2U: Built-in Dual-Array Microphone



NEW

DS-2CD2T23G2-2LI2U

DS-2CD2T23G2-4LI2U

DS-2CD2T43G2-2LI2U

DS-2CD2T43G2-4LI2U

DS-2CD2T63G2-2LI2U

DS-2CD2T63G2-4LI2U

- 1/2.8" Progressive Scan CMOS;
6 MP : 20fps(3200x1800), 4MP :
25fps/30fps(2688x1520), 2MP : 25fps/30fps
(1920x1080);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;
- 3D DNR; BLC/HLC; ICR; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect
cloud service
- *-2LI/4LI model: 3000K Warm LED; EXIR, up to
60m/80m
- *-2U: Built-in Dual-Array Microphone



NEW

DS-2CD2523G2-LI

DS-2CD2523G2-LIS2U

DS-2CD2543G2-LI

DS-2CD2543G2-LIS2U

DS-2CD2563G2-LI

DS-2CD2563G2-LIS2U

- 1/2.8" Progressive Scan CMOS;
H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR;
25fps/30fps(1920x1080);
- VCA functions; 3 streams;
- 3D DNR; BLC/HLC; ICR; 3000K Warm LED;
- EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect
cloud service;

*-S model: Audio/Alarm IO

*-2U: Built-in Dual-Array Microphone



DS-2CD2463G2-I

DS-2CD2443G2-I

DS-2CD2423G2-I

- 1/2.8" Progressive Scan CMOS;
H.265+/H.265/MJPEG;
- Color: 0.008 lux@ (F2.0, AGC ON), 0 lux with IR;
- 6MP : 12.5fps/15fps(3200x1800), 4MP : 25fps/30fps
(2688x1520), 2MP : 25fps/30fps (1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;
EXIR, up to 10m; DC12V&PoE;
- Built-in mic&speaker; Built-in micro SD/SDHC/
SDXC slot; HIK-Connect cloud service;



DS-2CD2563G2-I

DS-2CD2563G2-IS

DS-2CD2543G2-I

DS-2CD2543G2-IS

DS-2CD2523G2-I

DS-2CD2523G2-IS

- 1/2.8" Progressive Scan CMOS;
H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.005 lux@ (F1.6, AGC ON), 0 lux with IR;
- 6MP : 20fps(3200x1800), 4MP : 25fps/30fps
(2688x1520), 2MP : 25fps/30fps (1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;
EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot;
HIK-Connect cloud service; Built-in microphone
- (S) : Audio/Alarm IO

NEW

DarkFighterX

FOCUS
and
ACT

AcuSense Technology



NEW

DS-2CD2086G2H-I

DS-2CD2086G2H-IU

DS-2CD2046G2H-I

DS-2CD2046G2H-IU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2186G2H-I

DS-2CD2186G2H-ISU

DS-2CD2146G2H-I

DS-2CD2146G2H-ISU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2386G2H-I

DS-2CD2386G2H-IU

DS-2CD2346G2H-I

DS-2CD2346G2H-ISU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone



NEW

DS-2CD2T86G2H-2I

DS-2CD2T86G2H-4I

DS-2CD2T46G2H-2I

DS-2CD2T46G2H-4I

- 1/1.8" Progressive Scan CMOS;
25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light;
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; EXIR; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance



NEW

DS-2CD2686G2HT-IZS

DS-2CD2646G2HT-IZS

- 1/1.8" Progressive Scan CMOS;
25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *Junction box is included in the camera package



NEW

DS-2CD2786G2HT-IZS

DS-2CD2746G2HT-IZS

- 1/1.8" Progressive Scan CMOS;
25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
4MP:25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- *Junction box is included in the camera package

Live Guard

Perlindungan proaktif, sepanjang hari



NEW

DS-2CD2087G2H-LIU/SL

DS-2CD2047G2H-LIU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker



NEW

DS-2CD2387G2H-LISU/SL

DS-2CD2347G2H-LISU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker



NEW

DS-2CD2T87G2H-LISU/SL

DS-2CD2T47G2H-LISU/SL

- 1/1.8" Progressive Scan CMOS;
- 4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080,1280×720);4MP:25ps/30fps (2688× 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light
- VCA functions; 3 streams; 3D DNR; BLC; ICR;
- 3000K Warm LED;IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker



DS-2CD2086G2-IU/SL

DS-2CD2046G2-IU/SL

DS-2CD2026G2-IU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 Lux @ (F1.4, AGC ON), 0 lux with IR;
- 4K : 25fps/24fps(3840×2160), 4MP : 25fps/30fps (3200x1800, 2688x1520), 2MP : 25fps/30fps (1920x1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker



DS-2CD2047G2-LU/SL (ColorVu)

- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 lux @ (F1.0, AGC ON), 0 lux with LED on;
- 4MP : 25fps/30fps (2688x1520); 2MP : 25fps/30fps (1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- (U) : Built-in microphone
- (SL) : Built-in microphone and speaker



DS-2CD2386G2-ISU/SL

DS-2CD2346G2-ISU/SL

DS-2CD2326G2-ISU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200x1800, 2688x1520), 2MP : 25fps/30fps (1920x1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O



DS-2CD2T86G2-ISU/SL

DS-2CD2T46G2-ISU/SL

DS-2CD2T26G2-ISU/SL

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200x1800, 2688x1520), 2MP : 25fps/30fps (1920x1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O

Perangkat Keras Mutakhir

aperture super besar hingga F1.0
dan sensor canggih

Pemrosesan gambar yang terkini

Teknologi perintis 1SP menghasilkan
warna yang presisi untuk menampilkan
gambar yang jelas dan tajam hingga
130 dB WDR



Kehandalan Super Tinggi

Teknologi penyalarsan aktif menjamin
kinerja pemfokusan dalam produksi massal
produk ColorVu berdefinisi ultra tinggi



NEW

DS-2CD2087G2H-LI

DS-2CD2087G2H-LIU

DS-2CD2047G2H-LI

DS-2CD2047G2H-LIU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
4MP:25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- U: Built-in microphone



NEW

DS-2CD2187G2H-LI

DS-2CD2187G2H-LISU

DS-2CD2147G2H-LI

DS-2CD2147G2H-LISU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
4MP:25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 30m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- U: Built-in microphone



NEW

DS-2CD2387G2H-LI

DS-2CD2387G2H-LIU

DS-2CD2347G2H-LI

DS-2CD2347G2H-LIU

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
4MP:25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;
- U: Built-in microphone



NEW

DS-2CD2T87G2H-LI

DS-2CD2T47G2H-LI

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
4MP:25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;



NEW

DS-2CD2687G2HT-LIZS

DS-2CD2667G2HT-LIZS

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
6MP:25fps/30fps(3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps(3200 × 1800), 30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
- VCA functions; 3 streams;
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;



NEW

DS-2CD2787G2HT-LIZS

DS-2CD2767G2HT-LIZS

DS-2CD2747G2HT-LIZS

- 1/1.8" Progressive Scan CMOS;
4K:25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720);
6MP:25fps/30fps(3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps(3200 × 1800), 30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
2MP:25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720);
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0008 Lux @ (F1.2, AGC ON), 0 Lux with light
- VCA functions; 3 streams
- 3D DNR; BLC; ICR; 3000K Warm LED; IR, up to 40m DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;

ColorVu + Panoramic



Panoramic Cameras with ColorVu



180° Single-channel panoramic view with minimal distortion



Colorful imaging 24/7



Human and vehicle classification



Live Guard

ColorVu
TECHNOLOGY

AcuSense
TECHNOLOGY



NEW

DS-2CD2387G2P-LSU/SL (C)

DS-2CD2347G2P-LSU/SL (C)

- 4K:2*1/1.8" Progressive Scan CMOS; 20fps(5120*1440), 4 MP+4 MP resolution, 4MP:2*1/2.5" Progressive Scan CMOS; 25/24fps(3040*1368), 3 MP+3 MP resolution
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;
- VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K
- Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV



NEW

DS-2CD2T87G2P-LSU/SL (C)

DS-2CD2T47G2P-LSU/SL (C)

- 4K:2*1/1.8" Progressive Scan CMOS; 20fps(5120*1440), 4 MP+4 MP resolution, 4MP:2*1/2.5" Progressive Scan CMOS; 25/24fps(3040*1368) 3 MP+3 MP resolution
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;
- VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K
- Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV



DS-2CD2935FWD-IS

- 1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR;
- 5MP : 20fps(2944*1656), 25fps/30fps(2560*1440), 3MP : 25fps/30fps (2048*1536, 1920*1080);
- 1.16mm@F2.2, field of view: 180°(H)x180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 10m(optional); DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- (S) : built-in mic, Audio/Alarm I/O



DS-2CD2345G0P-I

- 1/2.7" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.028 lux @(F2.0, AGC ON), 0 lux with IR;
- 25fps/24fps (2688*1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service



DS-2CD2T45G0P-I

- 1/2.7" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.028 lux @(F2.0, AGC ON), 0 lux with IR;
- 25fps/24fps (2688*1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service



NEW

DS-2DE2C400MWG-E

DS-2DE2C200MWG-E

1/2.7, Progressive Scan CMOS

Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR

2.8 mm, horizontal FOV 105°, vertical FOV 58°, diagonal FOV 123°

4 mm, horizontal FOV 81°, vertical FOV 44°, diagonal FOV 97°

White Light Distance: up to 30 m IR Distance: up to 30 m

Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker



DS-2DE3404W-DE

DS-2DE3204W-DE

- High quality imaging with 4 MP / 2MP resolution
- Clear imaging against strong back lighting due to 120 dB WDR technology
- Pan and tilt ability enables camera to monitor zones of interest
- 4 × optical zoom allows for closer viewing of subjects in expansive areas
- Color: 0.1lux/F2.0, B/W:0.01lux/F2.0, Angle of View: 80-33.5 degree (Wide-Tele), Pan range: 0°~350°; Tilt range: 0°~90°(Auto Flip), PoE&12VDC



DS-2DE3A404IW-DE

- 4MP H.265+/H.265; 4x optical zoom; 120 dB WDR; 12VDC & PoE;
- Powered by DarkFighter; IP66 ;Up to 50 m IR distance
- Built-in speaker and microphone for audible warning and two-way audio;
- White light flashing when alarm triggers
- (/W) : Wifi



DS-2DE3A400BW-DE

- 4MP H.265+/H.265; 120 dB WDR; 12VDC & PoE;
- ColorVu; IP66 ;
- Built-in speaker and microphone for audible warning and two-way audio;
- White light flashing when alarm triggers
- Accurate human and vehicle target classification and alarm, based on deep learning algorithm
- Support face capture. Up to 5 faces captured at the same time



DS-2DE2A404IW-DE3(2.8-12mm)

- 4MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264 codec 3D DNR, ICR, Color:
- 0.005lux/F1.6, B/W:0.001lux/F1.6,
- 4x optical zoom, Angle of View: 100° to 33° (Wide-Tele), Digital Zoom: 16X,
- 4MP : 2560 × 1440:30fps, Pan range: 0°~330°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1°~100°/s, Tilt Speed: 0.1°~100°/s, 20m IR, POE&12VDC



DS-2DE4425IW-DE

DS-2DE4225IW-DE

DS-2DE4215IW-DE

- 4MP, 1/2.5" CMOS, H.265+/H.265/H.264+/H.264 codec, 3D DNR, True WDR,
- Ultra-low light Powered By DarkFighter
- Color: 0.005lux/F1.6, B/W:0.001lux/F1.6,
- Optical Zoom: 25x/15x, Digital Zoom: 16X100m IR
- 4MP : 2560*1440:30fps; 2MP : 1920*1080:30fps.
- Pan Speed: 0.1°~80°/s, Tilt Speed: 0.1°~80°/s, PoE&12VDC
- Smart Detection



DS-2DE4A225IW-DE

DS-2DE4A425IW-DE

- High quality imaging with 4MP / 2MP resolution
- Excellent low-light performance via powered-by-DarkFighter technology
- Clear imaging against strong back lighting due to 120 dB WDR technology
- Pan and tilt ability enables camera to monitor zones of interest
- 25x optical zoom allows for closer viewing of subjects in expansive areas
- Up to 50m IR range ensures safety at night
- Water and dust resistant (IP66)



DS-2DE5225W-AE

DS-2DE5225W-AE3

- 4MP, 1/2.5" CMOS, H.265+/H.265/H.264+/H.264 codec, 3D DNR, True WDR,
- Ultra-low light Powered By DarkFighter
- Color: 0.005lux/F1.6, B/W:0.001lux/F1.6,
- Optical Zoom: 25x/15x, Digital Zoom: 16X100m IR
- 4MP : 2560*1440:30fps; 2MP : 1920*1080:30fps. Pan Speed: 0.1°~80°/s, Tilt Speed: 0.1°~80°/s, PoE&12VDC
- Smart Detection



DS-2SE4C215MWG-E

DS-2SE4C225MWG-E

DS-2SE4C415MWG-E

DS-2SE4C425MWG-E

- Captures a large area and great details at the same time
- High quality imaging with 4 MP/2 MP resolution
- Excellent low-light performance with powered by DarkFighter technology and ColorVu technology
- Secures an expansive area with 15x / 25x optical zoom and 16 × digital zoom
- Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus
- Expansive night view with up to 100 m IR distance & 30 m white light
- Supports 12 VDC & PoE+



KATALOG RETAIL 2024